

Submittal Data: Wall Mounted Split-System

Model: ACE24HP220/ACC24HP220

Style: Cool with Heat Pump

Job Name:	Location:	
Purchaser:		
Engineer:		
Submitted To:		For: ☐ Reference ☐ Approval ☐ Constructio
Submitted By:		
Unit Designation:	Schedule Number:	Model Number:

Capacities:					
Cooling	Btu/Hr	24,000			
Heating	Btu/Hr	24,000			
Cooling/Heating Current	Amps	8.5/8.0			
SEER	13.0				
Average Cooling Capacity	1,200				
Indoor Unit					
Rated Voltage	Volts	220			
Rated Frequency	Hertz	60			
Noise Level	dB(a)	44			
Weight	Lbs	44			
Air Flow Rate	CFM	715			
Outdoor Unit:					
Power Supply	Volts	220			
Breaker Size	Amps	15			
Cooling/Heating Power	Watts	1,930			
Weight	Lbs	143			
Refrigerant	Type	R410A			
Refrigerant Piping:					
Max Height Difference	Feet	16.5			
Max Total Length	Feet	50			
Discharge Liquid Line	Inch	3/8"			
Suction Line	Inch	5/8″			
Drain Line	Inch	1/2″			

Outline and Dimensions

Indoor Evaporator


Depth: 8.9 in. Width: 48.6 in. Height: 12.8 in.

Outdoor Condenser

Depth: 13.0 in. Width: 35.4 in. Height: 33.0 in.



Power Connection Wiring Diagram



Standard Features:

- Five Year Compressor Warranty
- (Opt) Low Ambient Control Kit
- "Dry" Mode Dehumidification
- 24-Hour Programmable Timer
- Cold Catalyst Sterilization Filter
- Three Year PC Board Warranty
- LCD Wireless Remote
- Energy Saving "Sleep" Mode
- 3 Stage Indoor Fan Speed
- Self-Diagnosis Operation
- One Year Parts Warranty
- Outdoor Golden Fin Treatment
- Indoor Hydrophilic Coated Fins
- Heavy-Gauge Galvanized Steel
- Outlet Air Directional Control

<u>Notes:</u>			
		·	